



# HITACHI 3.8 TONNE EXCAVATOR



## Features and Benefits:

### High productivity

The ZX38U-6 delivers high levels of productivity on the job site thanks to a powerful Stage V-compliant engine, quick cycle time and an efficient hydraulic system.

### Built to last

Durable features of the ZX38U-6 – such as strengthened front joints, reinforced D-frame and boom cylinder guard – ensure a reliable performance, helping you to get the job done on time and on budget.

### Lower fuel costs

The advanced energy-saving system combines ECO mode, auto idle and isochronous control features to significantly reduce fuel consumption. It also reduces noise levels and emissions.

## Specifications:

- Weight 3.96 t
- Transport length 4.76 m
- Transport width 1.74 m
- Transport height 2.48 m
- Bucket capacity 0.1 m<sup>3</sup>
- Bucket width 0.4 m
- Track width 300 mm
- Driver protection KbR
- Max. Reach horizontal 5,41 m
- Dredging depth 3.46 m
- Tear-out force 27.1 kN
- Engine manuf. Yanmar
- Engine type 3TNV88
- Engine power 21.2 kW
- Displacement 1.642 l
- Revolutions at max torque 1440 rpm

**PEG Australia**

ABN 89 651 994 740

+61 404 116 670

operations@pacificenergygroup.com.au

260 Lion Creek Road, Rockhampton, Qld, Australia, 4700

www.pegaustralia.com.au

