



JLG 4017PS TELEHANDLER

Features and Benefits:



- Compliant with latest standards in the industry: With a dependable Deutz Tier IIIb engine (75 kW/100 hp), you are ensured to be compliant with the latest standards in environmental regulations. Each handler is equipped with EN15000 as well, for safe operation during loading and placement activities.
- Designed with the operator in mind: The new handlers are designed to be true drivers' machines. A lot of attention has been paid during the design stage on intuitive controls and self-explanatory indicator panels and dashboard. Swift response of lift and lower functions due to improved oil flow in boom and proportional controls help further improve daily output on jobsites.
- Robust and easy to maintain: the outer section of the boom is reinforced with double plated steel and the boom head is actually thickened to ensure your handler is more resistant to every day jobsite wear and tear when working frequently with buckets. Maintenance can be done relatively trouble free as well; grease points in the boom are grouped, main components are easily accessible and the engine is mounted to the side which provides good access for service engineers.

Specifications:



Model Name / Number	4017PS
Brand	JLG
Maximum Lift Capacity	4000 kg
Maximum Lift Height	17.30 m
Length (Less Forks)	6.67 m
Width	2.44 m
Height	2.63 m
Wheelbase	3.20 m
Ground Clearance	0.47 m
Usage/Application	Commercial
Fuel Type	Diesel
Maximum Reach	12.70 m
Maximum Range	12.5 m
Transmission	4 Speed forward - 3 reverse powershift transmission; 4-Wheel Drive
Tyres	Standard - Mitas 14.00-24 TG02
Steering 4-Wheel	Power steering with steering wheel spinner Two wheel/Four Wheel/Crab Steer with Rear Wheel Assisted alignment

PEG Australia

ABN 89 651 994 740

+61 404 116 670

operations@pacificenergygroup.com.au

260 Lion Creek Road, Rockhampton, Qld, Australia, 4700

www.pegaustralia.com.au

