



SPIDER 22.10 EVO MONITOR LIFT WITH DEAN TRAILER



Features and Benefits:

The Monitor 2210 EVO Spider Lift is equipped with an excellent up-and-over reach with modern double-knuckle technology, and adjustable fly-jib for extra maneuverability.

It has the most unique ability to rotate a complete 360° even when the stabilizer legs are set in their narrow position. With the basket removed and tracks in narrow position, the 2210 Evo allows for doorway access. Weighing in at only 3 t, this 22 m Spider Lift is ideally suited for use on load-sensitive surfaces.

The radio control feature allows all functions to be controlled from the basket (or any other position). This includes driving, setting the stabilizer legs and operating the booms, making the 2210 Evo exceptionally operator-friendly.



Specifications for Spider 22.10 Evo Monitor Lift:

- Max. Working Height: 21.70 m
- Max. Working Reach: 10.30 m
- Capacity: 230 kg
- Chassis Type: Crawler Tracks
- Hydraulic Fly Boom: Yes
- Platform Rotation: Yes
- Weight/Outreach Limited: Yes
- Turret Rotation: 365
- Outrigger Stabilisers: Yes
- Min. Transport Length: 5.63 m
- Min. Transport Width: 0.95 m
- Min. Transport Height: 2.07 m
- Power: Kubota 14 Hp Diesel & 240v Electric System
- Weight: 2,980 kg



Specifications for Plant Trailer for Transport of Spider 22.10 Evo Monitor Lift:

- 4.5 Tonne ATM
- Electric Brakes
- Led Lights
- Pull Out Ramps
- Tilt Frame for loading and unloading of Spider
- Tie Down Points Along both of Trailer Sides
- Tandem Axle
- Spring Suspension
- Heavy duty construction

PEG Australia

ABN 89 651 994 740

+61 404 116 670

operations@pacificenergygroup.com.au

260 Lion Creek Road, Rockhampton, Qld, Australia, 4700

www.pegaustralia.com.au

